

Next stop: LAPP

Connection solutions for railway technology

More products, faster selection, everything at a glance



Fast track: Discover our railway products in the new product overview – so that you can get to your destination faster.

Millions of people around the world travel by train each day. Increasing urbanisation in many major cities means that mobility needs to be rethought and the demand for public transport is growing. Passenger numbers on rail services are on the rise – and with them, so are the expectations for the accessibility, punctuality, safety and reliability of rail transport. The cables that are used play a major

part in determining whether these expectations are met. **That is why LAPP supplies you with tested and certified system solutions for railway technology from a single source – now with even greater variety.** We draw on our decades of experience to support you with advice and provide you with exactly the solution you need.

OUR PRODUCT SOLUTIONS FOR RAIL TRANSPORT

- 1 Braking system
- 2 Driver's desk
- 3 Traction converter
- 4 Control cabinets
- 5 Coupling
- 6 Train control
- 7 Drive motor
- 8 Braking system



- 9 Fan
- 10 Battery
- 11 Auxiliary converter
- 12 Passenger information system
- 13 WC
- 14 Lighting
- 15 Air conditioning
- 16 Doors

RELIABLY TO THE DESTINATION

Connection solutions for rail transport need to meet specific requirements – you can always depend on quality with LAPP:

- Our cables have electron beam or chemical cross-linking and so offer **maximum resistance** to chemical and mechanical stress, UV light and high temperatures.
- When it comes to passenger transport, safety is the top priority. Most of our products are fire proof at the **hazard level HL3 according to DIN EN 45545-2** to ensure that people and goods are safe.
- Our production site in South Korea guarantees you **process reliability with IRIS ISO/TS 22163:2017 certification.**
- We monitor the quality of all our products in our **in-house testing laboratories.**

POWER AND CONTROL CABLES

Standard	Type	Nominal voltage U_0/U (EN50306 not applied) [V]	Shielding	Twisted-Pair	Conductor stranding	Number of cores from – to	Conductor cross-section from – to [mm ²]	Hazard level (HL) EN45545-2	Temperature range from – to [°C]	Product name	
EN 50306-2		300/500 (600/1000)			19/37 wires	1	0.5 – 2.5	1 – 3	-50 – +125	ÖLFLEX® TRAIN 301 TW	
EN 50306-4	1P	300/500 (600/1000)	•	•	19/37 wires	2 – 48	0.5 – 2.5	1 – 3	-50 – +125	ÖLFLEX® TRAIN 310 TW-P	
	3P					ÖLFLEX® TRAIN 315 C TW-P					
	5P					ÖLFLEX® TRAIN 317 C TW-P					
	1E					ÖLFLEX® TRAIN 320 TW-E					
	3E					ÖLFLEX® TRAIN 325 C TW-E					
	5E					ÖLFLEX® TRAIN 327 C TW-E					
EN 50264-3-1	M	600/1000			5	1	0.5 – 300	1 – 3	-50 – +120 (145 for 3,000 h)	ÖLFLEX® TRAIN 331 600V	
	MM	1800/3000					1.5 – 300		-50 – +120	ÖLFLEX® TRAIN 361 1,8kV	
		3600/6000					2.5 – 300		ÖLFLEX® TRAIN 371 1,8kV		
EN 50264-3-2	MM	600/1000	•	5	2 – 40	1	0.5 – 50	1 – 3	-50 – +120	ÖLFLEX® TRAIN 381 3,6kV	
	MMS									ÖLFLEX® TRAIN 340 600V	
	MM	300/500	•							1 – 2.5	ÖLFLEX® TRAIN 345 C 600V
	MMS										ÖLFLEX® TRAIN 350 300V
EN 50382	F	1800/3000			5	1	1.5 – 240	1 – 3	-40 – +150	ÖLFLEX® TRAIN HT 150 F 1,8 kV	
	FF						2.5 – 240			ÖLFLEX® TRAIN HT 150 FF 1,8 kV	
	F	3600/6000					1.5 – 240			ÖLFLEX® TRAIN HT 150 F 3,6 kV	
	FF						2.5 – 240			ÖLFLEX® TRAIN HT 150 FF 3,6 kV	
	FX						6			50 – 185	ÖLFLEX® TRAIN HT 150 FX 3,6 kV
4GKW	M	1800/3000			5	1	1.5 – 300	1 – 3	-40 – +125	ÖLFLEX® TRAIN 4GKW	

Product Overview

DATA COMMUNICATION SYSTEMS

Product type	MVB	WTB	Ethernet Cat.5e	Ethernet Cat.6 _A	Ethernet Cat.7	Outer diameter [mm]	Number of cores and mm ² per conductor	Temperature range from - to [°C]	Characteristic impedance [Ω]	Hazard level (HL) EN45545-2	Product name
Bus-Cables	•					7.6	1 x 2 x 0.5	-45 - +90	120	1 - 3	UNITRONIC® TRAIN
							1 x 2 x 0.5 + 0.5				
						8.3	2 x 2 x 0.5				
						8.1	2 x 2 x 0.5 + 4 x 0.25				
		•				8.4	1 x 2 x 0.75				
Ethernet-Cables			•			6.5	1 x 4 x AWG22 / 7	-45 - +90	100	1 - 3	ETHERLINE® TRAIN
						7.6	1 x 4 x 0.5 / 7				
						7.7					
						8.4	4 x 2 x AWG24 / 7				
						8.4					
			•								

CABLE GLANDS

Product type	Plastic black	Plastic light grey	Nickle plated brass	EMC design (360° brass brush)	EMC design (contact spring)	Bend protection + strain relief	For connector cut-outs size 24	Size from - to	Clamping range from - to [mm]	Number of cables	Hazard level (HL) EN45545-2	Brass lead-free on request	Product name
Cable gland	•	•	•	•	•	•	•	M12 - M63	4.0 - 45.0	1	1 - 3	•	SKINTOP® ST-HF-M
									3.5 - 45.0				SKINTOP® MS-HF-M
								M12 - M50	3.5 - 35.0				SKINTOP® MS-HF-M SC
								M25 - M63	9.0 - 45.0				SKINTOP® MS-HF-M BRUSH
								M16 - M32	4.5 - 21.0				SKINTOP® MS-HF-M GRIP
Mutli cable bushing system with gel technology	•						•		2.0 - 20.0	11 - 30	2*		SKINTOP® MULTI
								M40 - M63	1.0 - 6.0				12 - 30

* On request

Product Overview

PROTECTIVE CABLE CONDUIT SYSTEMS

Product type	PA 6	PA 12	Standard version	Heavy duty version	Divisible version	Black	Grey	Nominal size from – to	Plastic thread from – to	Metal thread from – to	Angled – °	Increased chemical resistance	Hazard level (HL) EN45545-2	Integrated SKINTOP® cable gland	Easy assembly	Mounting holes	Product name															
Corrugated conduit	•		•	•	•	•	•	7 – 125				•	1 – 3				FIPLOCK® PA6															
								17 – 48									FIPLOCK® PA6 - SPLIT															
								7 – 45									FIPLOCK® PA12															
	7 – 170	FIPLOCK® PA12 - SPLIT																														
	7 – 48																															
	7 – 100																															
Conduit fitting	•					•	•	7 – 48	M12 – M63		90°	•	1 – 3	•			FIPLOCK® ONE M															
								10 – 48	M12 – M63								FIPLOCK® ONE 90° M															
								10 – 29	M16 – M63								FIPLOCK® ONE Metal M															
								10 – 48	M16 – M32								FIPLOCK® ONE ST-M															
								10 – 48	M12 – M50								FIPLOCK® ONE CLICK-M															
								7 – 48	PG7 – PG48								FIPLOCK® ONE MS-M															
								7 – 48	PG7 – PG48								FIPLOCK® ONE PG															
								12 – 48	PG9 – PG48								FIPLOCK® ONE 90° PG															
								10 – 48	NPT3/8" – NPT2"								FIPLOCK® ONE Metall PG															
								10 – 29	NPT3/8" – NPT1"								FIPLOCK® ONE NPT															
								10 – 48	NPT1/4" – NPT2"								FIPLOCK® ONE ST-NPT															
								10 – 48									FIPLOCK® ONE MS-NPT															
								T-divider	•											•	•	•	10 – 48				•	1 – 3				FIPLOCK® ONE-T
								T-adapter															FIPLOCK® ONE-TA									
								Y-divider															FIPLOCK® ONE-Y									
Reducer	FIPLOCK® ONE-R																															
Coupler	FIPLOCK® ONE-C																															
Coupler for smooth pipes	FIPLOCK® ONE-CS																															
Metal conduit with PUR jacket			•					5/16" – 1 1/2"				•	1 – 2				SILVYN® HFX-V0															
								12 – 50									SILVYN® ZHLS															
Metal conduit with polyolefin jacket			•					1/4" – 2"				•	1 – 2				SILVYN® FCE-V0															
								12 – 50									SILVYN® FCE-LFH															
Fireproof cable protection conduit								6 – 102					1 – 3				SILVYN® HIPROJACKET															

Product Overview

CABLE MARKING PRODUCTS

Product type	Properties	Dimensions [mm]	Length / max. characters	Customer-specific labeled	Mounting		Colour				Additional colours on request	Product name
					Cable tie	Screw hole	Natural	Yellow	White	Black		
Customized embossed stainless steel marking system	Single-lined	Height: 9.9	15	•	•	•	•					FLEXIMARK® Stainless steel FCC
			30									
	Double-lined	Height: 13.9	25									
			50									
Manual embossing machine	Aluminium / stainless steel embossing machine	Height: 12			•	•	•					M1011 Manual embossing machine
Stainless steel cable marking plain	Material: AISI-316	Height: 11	75 - 110 mm		•	•	•					SP Metal print
Pre-cutted chrink tube marker	Shrink ratio: 2:1	Diameter: 1.2 - 50.8	12 - 50 mm					•			•	FLEXIMARK® Organized shrink tube
Thin walled shrink tube	EN45545-2 HL 1-3, LUL1-085 A3, Boeing BSS7239 shrink ratio: 2:1	Diameter: 0.6 - 25.4						•	•	•	•	Shrink tube PROTECT-HF RW
Self-adhesive Safety signs	Warning, prohibition and mandatory signs acc. to EN ISO 7010	Side lenght / Diameter: 25 / 50 / 100										FLEXIMARK® Safety signs

Product Overview

EPIC® RECTANGULAR CONNECTORS

Product type	Connection type				Number of contacts	Wire cross-section [mm ²]	Rated voltage [V]			Rated current [A]			Hazard level(HL) EN45545-2	Product name
	Crimp	Push-In	Cage clamp	Screw			IEC	UL/USR	CSA/CNR	IEC	UL/USR	CSA/CNR		
Inserts standard				•	3 - 48	0.5 - 2.5	400	600	600	23	10	10	1 - 3	EPIC® H-A
	•	•		•	6 - 48	0.14 - 4.0	500	600	600	16	16	16		EPIC® H-BE
				•	6 - 12	0.5 - 6.0	500	600	600	35	35	35		EPIC® H-BS
				•	3+2 - 6+2	0.5 - 2.5	630	600	600	16	16	16		EPIC® H-BVE
Inserts modular	•	•	•	•	1 - 36	0.09 - 95.0	up to 1000			up to 250				EPIC® MH MODULAR

Product Overview

ACCESSORIES

Product type	Properties	Dimensions	Product name
Thin walled shrink tube	Colours: black, yellow, white EN45545-2 HL 1-3, LUL1-085 A3, Boeing BSS7239 shrink ratio: 2:1	Diameter: 0.6 – 25.4 mm	Shrink tube PROTECT-HF RW
Cable tie with steel nose	Material: PA6.6, Colour: natural EN45545-2 HL 1-3, NFF 16-101: I3F1	92.0 x 2,4 – 340.0 x 7.0 mm	TY-RAP® Railway
Stainless steel cable tie	Material: AISI 316 corrosion and chemical resistant	4.6 x 100 – 7.9 x 1010 mm	LS steel cable ties
Tube cable lugs with inspection hole	For fine and multi-wire copper conductors (class 2 and 5)	0.75 – 10 mm ²	Tube cable lugs KR
	For multi-wire copper conductors (class 2)	10 – 1,000 mm ²	Tube cable lugs KRT
	For fine wire copper conductors (class 2, 5 and 6)	16 – 800 mm ²	Tube cable lugs KRF
Tube cable lug with inspection hole and narrow flange	With narrow flange for fine wire copper conductors class 2, 5 and 6, especially for mounting through cable glands	50 – 240 mm ²	Tube cable lugs KRFS
EMC shield clamp	Mounting directly on 35mm DIN rails	Clamping range: 3 – 18 mm	Shield clamp EMC-Guard
EMC copper braid	Tinned-copper	Diameter 1 – 50 mm	Copper braid
Copper flat ground straps	Strands made of tinned-copper wires, welded ends or assembled with pressed contact sleeves	Cross-section: 6 / 10 / 16 / 25 mm ² Length: 200 / 300 / 500 mm	Flat Ground Straps
Two-part screen connector	Inner sleeve absorbs the pressure and thereby protects the inner conductor against mechanical stress	for shielded cables from 1.1 to 9.4 mm dielectric diameter (diameter under the shield)	SHIELD-KON® - Inner Sleeves
	Hexagonal crimping of the outer sleeve guarantees a gas-tight electrical and mechanical connection		SHIELD-KON® - Outer Sleeves

CONNECT NOW

You would like to learn more about our reliable connection solutions for railway technology? We will be happy to provide you with expert advice.

U.I. Lapp GmbH

Schulze-Delitzsch-Straße 25 · 70565 Stuttgart
Tel.: 0711 7838-01 · Fax: 0711 7838-2640
www.lapp.com/en/de · info.de.uil@lapp.com

Learn more about our connection solutions at
www.lapp.com/en/de/e/000061

